

AFR8600 Series Biometric Readers with Optical Sensor

The **AFR8600 Series** is a family of biometric fingerprint readers comprising of,

- AFR8620W Biometric Reader only
- AFR8631W Biometric Reader w/keypad & LCD

The AFR8600 Series Biometric Smartcard operates on a widely recognized industry 3-factor authentication for the highest level of security with the simultaneous authentication of WHO you are (fingerprint), WHAT you have (card) and WHAT you know (PIN). This reader offers unmatched versatility that allows user authentication via (Fingerprint, Card and PIN), (Fingerprint and Card), (Fingerprint and PIN) and (Fingerprint only).



AFR8620W




AFR8631W

Key Features

- Integrated optical fingerprint sensor, contactless smartcard and keypad offer multiple combinations of fingerprint/card/PIN access modes for various levels of security requirements
- Supports up to 4,500 users with 2 fingerprint templates per user in fingerprint only mode
- Modern & elegant designer casing to suit any decor
- 1:1 and 1:N user authentication modes
- Rapid fingerprint verification of less than 2.0s
- Large LCD display for easy viewing (AFR8631)
- Supports industry standard contactless smartcard read/write operations in compliance with ISO 14443 Type A

System Diagram



Technical Specifications

Specifications*	AFR8620W	AFR8631W
Description	Biometric Reader only	Biometric Reader w/keypad & LCD
Read Range	2"/50 mm	
Communication Interface	Wiegand 34-bits, Ethernet (Template Download)	
LED Indicator	Blue/Red	Green/Red
Buzzer	Multitone	
LCD Display	-	128 x 64 Graphics LCD with backlight
Keypad	-	17 Silicon keys with illumination
Sensor Type	Optical	
Sensor Array	272 x 320	
Sensor Resolution	500 dpi	
Template Size	256 - 384 bytes	
Reader Technology	MIFARE (ISO 14443 Type A)	
Tamper Detection	Yes	No
Users	4,500	
Event Buffers	32,768	
Fingerprint Templates	2 per User	
Verification	< 2s	
False Acceptance Rate (FAR)	0.00%	
False Rejection Rate (FRR)	0.01%	
Termination	Pigtail Cable	
Mounting	Surface mount	
Color	Black & Silver	
Input Voltage	9 - 24 VDC	
Current Consumption	500 mA at 12 VDC max	1000 mA at 12 VDC max
Dimensions (H x W x D)	160 x 56.9 x 40.1 mm	130 x 145 x 45 mm
Weight	150 g	440 g
Operating Temperature	0°C to 65°C	0°C to 55°C

*Specifications are subject to change without prior notice

Ordering Information

Model No.	Description
AFR8620W	AFR8620 Biometric Reader only
AFR8631W	AFR8631 Biometric Reader w/keypad & LCD