


ELV Column Speakers

Controlled Sound Dispersion and Weatherproof Performance



ELV T-70xA series Column Speakers provide a combination of controlled sound dispersion, aesthetic appeal, and robust weatherproof construction (IP66). Ideal for applications where targeted sound coverage is needed, especially in reverberant indoor spaces or outdoors, these speakers minimize unwanted sound spill above and below the unit. Available in four power ratings (10W to 40W @100V), they feature multiple drivers in a slim aluminum enclosure and include mounting brackets.



T-701A T-702A T-703A T-704A

Key Features

- **Multiple Power Options:** Choose from 10W, 20W, 30W, or 40W models (with lower power taps available) to suit application needs.
- **Weatherproof Design:** IP66 rating allows for reliable use both indoors and outdoors.
- **Durable Aluminum Body:** Robust enclosure with aluminum grille ensures longevity.
- **Controlled Dispersion:** Columnar driver arrangement focuses sound projection horizontally, reducing vertical dispersion – improving clarity in reverberant spaces.
- **Clear Audio Quality:** Good frequency response for both voice and background music applications (down to 130-150Hz).
- **Aesthetically Pleasing:** Slim design integrates well architecturally.
- **Easy Installation:** Includes mounting bracket fixed by screw.

Applications

Houses of worship, lecture halls, transportation platforms, corridors, convention centers, outdoor patios, swimming pool areas, and other spaces benefiting from controlled sound projection and weather resistance.

System Compatibility

- **Amplifiers:** Compatible with any ELV 70V/100V amplifier output (A-XXXXR series, A-XXXXD series).
- **Volume Controls:** Can be used with A-C30R (check power load per control).

Technical Specifications

Specification	T-701A	T-702A	T-703A	T-704A
Description	10W IP66 Column Speaker	20W IP66 Column Speaker	30W IP66 Column Speaker	40W IP66 Column Speaker
Power Taps @ 100V	10W, 5W	20W, 10W	30W, 15W	40W, 20W
Drivers	2×2.5"	4×2.5"	6×2.5"	8×2.5"
SPL (1W/1m)	88dB ±3dB	89dB ±3dB	91dB ±3dB	92dB ±3dB
Frequency Response	150Hz - 16kHz	130Hz - 16kHz	130Hz - 16kHz	130Hz - 16kHz
IP Rating	IP66			
Material	Aluminum Body/Grille			
Dimensions	265 x 105 x 75 mm	410 x 105 x 75 mm	550 x 105 x 75 mm	690 x 105 x 75 mm
Weight	1.4 kg	2.2 kg	2.9 kg	3.7 kg

**Specifications are subject to change without prior notice*

Ordering Informations

Model No.	Description
T-701A	10W IP66 Column Speaker
T-702A	20W IP66 Column Speaker
T-703A	30W IP66 Column Speaker
T-704A	40W IP66 Column Speaker